



Aalborg Universitet

AALBORG UNIVERSITY  
DENMARK

## mitolina

*MITOchondrial LINEage Analysis*

Andersen, Mikkel Meyer

*Published in:*  
The Journal of Open Source Software

*DOI (link to publication from Publisher):*  
[10.21105/joss.01266](https://doi.org/10.21105/joss.01266)

*Creative Commons License*  
CC BY 4.0

*Publication date:*  
2019

*Document Version*  
Publisher's PDF, also known as Version of record

[Link to publication from Aalborg University](#)

*Citation for published version (APA):*  
Andersen, M. M. (2019). mitolina: MITOchondrial LINEage Analysis. *The Journal of Open Source Software*, 4(34), [1266]. <https://doi.org/10.21105/joss.01266>

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal -

### Take down policy

If you believe that this document breaches copyright please contact us at [vbn@aub.aau.dk](mailto:vbn@aub.aau.dk) providing details, and we will remove access to the work immediately and investigate your claim.

# mitolina: MITOchondrial LINEage Analysis

Mikkel Meyer Andersen<sup>1</sup>

<sup>1</sup> Department of Mathematical Sciences, Aalborg University, Denmark

DOI: [10.21105/joss.01266](https://doi.org/10.21105/joss.01266)

## Software

- [Review](#) ↗
- [Repository](#) ↗
- [Archive](#) ↗

Submitted: 18 February 2019

Published: 21 February 2019

## License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC-BY](#)).

## Summary

This R (R Core Team, 2018) package, **mitolina** (**MITO**chondrial **LINE**age Analysis), contains functionality to simulate and analyse populations of mitochondrial genomes (mitogenomes). This is achieved using both R and C++ via Rcpp (Eddelbuettel & Balamuta, 2017) for efficient computations.

Mitochondria are of interest for example in forensic genetics as they are very resistant to degradation and it is sometimes possible to construct a mitochondrial DNA profile when it is not possible to construct a traditional DNA profile (Andersen & Balding, 2018; Butler, 2009). This happens for example when the biological sample does not contain cell nuclei or when the sample is degraded (for example by time or environment).

Just as DNA profiles based on the Y chromosome are paternal lineage markers (inherited from fathers to boys) (Andersen & Balding, 2017; Butler, 2009), then DNA profiles based on the mitogenome are maternal lineage markers (inherited from mothers to children) (Andersen & Balding, 2018; Butler, 2009). This software operates under the maternal inheritance only model, i.e. that mtDNA is only passed on by mothers to children. It is often helpful to perform simulations of populations in lineage marker research as recent research on using Y chromosomal DNA profiles in forensic genetics demonstrate (Andersen, 2018; Andersen & Balding, 2017; Andersen, Caliebe, Jochens, Willuweit, & Krawczak, 2013; Andersen, Eriksen, & Morling, 2013).

This R package, **mitolina**, is based on the R package **malan** (Andersen, 2018) that simulates populations of Y chromosomes. The packages are fundamentally different in two aspects caused by the way that paternal and maternal lineage markers behave genetically. For example, with the mitogenome it is necessary to simulate both females and males (as males have their mother's mitogenome), at least in the generations where the profiles must be used. Also, the genetic DNA profiles used in forensic genetics are different for the two types of lineage markers. A mitogenomic DNA profile can be seen as a profile of many thousands binary markers whereas a Y-profile consists of 10-20 integer valued markers.

The simulation model allows for flexible simulations by first simulating a genealogy (with population sizes at each generation specified by a vector for number of females and a vector for number of males) with various parameters such as variance in reproductive success (Andersen & Balding, 2017). It is possible to impose mitogenomes in various ways and several sets of mutation rates are included (Översti et al., 2017; Rieux et al., 2014; Soares et al., 2009). There are also 588 forensic-quality haplotypes representing three U.S. populations from (Just et al., 2015) included; they can for example be used to distribute founder haplotypes.

The **mitolina** software makes it possible to query the population and its individuals in multiple ways. For example to count the number of females or males in the population



**Figure 1:** Simulation illustration.

with a certain mitogenome. Or obtain the distribution of number of meioses between a queried contributor and the individuals in the population with a matching mitogenome.

The documentation of `mitolina` consists of manual pages for the various available functions, an article describing how to use the package (*vignette*), and unit tests.

Research using this software in interpretation of DNA profiles based on the mitogenome in forensic genetics is already published (Andersen & Balding, 2018) and the aim is that this software can help further research in this important topic.

I would like to thank David J Balding for helpful discussions.

## References

- Andersen, M. M. (2018). malan: MAle Lineage ANalysis. *The Journal of Open Source Software*, 3(25). doi:[10.21105/joss.00684](https://doi.org/10.21105/joss.00684)
- Andersen, M. M., & Balding, D. J. (2017). How convincing is a matching Y-chromosome profile? *PLOS Genetics*, 13(11), e1007028. doi:[10.1371/journal.pgen.1007028](https://doi.org/10.1371/journal.pgen.1007028)
- Andersen, M. M., & Balding, D. J. (2018). How many individuals share a mitochondrial genome? *PLOS Genetics*, 14(11), e1007774. doi:[10.1371/journal.pgen.1007774](https://doi.org/10.1371/journal.pgen.1007774)
- Andersen, M. M., Caliebe, A., Jochens, A., Willuweit, S., & Krawczak, M. (2013). Estimating trace-suspect match probabilities for singleton Y-STR haplotypes using coalescent theory. *Forensic Science International: Genetics*, 7(2), 264–271. doi:[10.1016/j.fsigen.2012.11.004](https://doi.org/10.1016/j.fsigen.2012.11.004)
- Andersen, M. M., Eriksen, P. S., & Morling, N. (2013). The discrete Laplace exponential family and estimation of Y-STR haplotype frequencies. *Journal of Theoretical Biology*, 329, 39–51. doi:[10.1016/j.jtbi.2013.03.009](https://doi.org/10.1016/j.jtbi.2013.03.009)
- Butler, J. M. (2009). *Fundamentals of Forensic DNA Typing*. Academic Press.

Eddelbuettel, D., & Balamuta, J. J. (2017). Extending *R* with *C++*: A Brief Introduction to *Rcpp*. *PeerJ Preprints*, 5, e3188v1. doi:[10.7287/peerj.preprints.3188v1](https://doi.org/10.7287/peerj.preprints.3188v1)

Just, R. S., Scheible, M. K., Fast, S. A., Sturk-Andreaggi, K., Röck, A. W., Bush, J. M., Higginbotham, J. L., et al. (2015). Full mtGenome reference data: Development and characterization of 588 forensic-quality haplotypes representing three U.S. populations. *Forensic Science International: Genetics*, 14, 141–155. doi:[10.1016/j.fsigen.2014.09.021](https://doi.org/10.1016/j.fsigen.2014.09.021)

Översti, S., Onkamo, P., Stoljarova, M., Budowle, B., Sajantila, A., & Palo, J. U. (2017). Identification and analysis of mtDNA genomes attributed to Finns reveal long-stagnant demographic trends obscured in the total diversity. *Scientific Reports*, 7. doi:[10.1038/s41598-017-05673-7](https://doi.org/10.1038/s41598-017-05673-7)

R Core Team. (2018). *R: A language and environment for statistical computing*. Vienna, Austria: R Foundation for Statistical Computing. Retrieved from <https://www.R-project.org/>

Rieux, A., Eriksson, A., Li, M., Sobkowiak, B., Weinert, L. A., Warmuth, V., Ruiz-Linares, A., et al. (2014). Improved Calibration of the Human Mitochondrial Clock Using Ancient Genomes. *Molecular Biology and Evolution*, 31(10), 2780–2792. doi:[10.1093/molbev/msu222](https://doi.org/10.1093/molbev/msu222)

Soares, P., Ermini, L., Thomson, N., Mormina, M., Rito, T., Röhl, A., Salas, A., et al. (2009). Correcting for Purifying Selection: An Improved Human Mitochondrial Molecular Clock. *American Journal of Human Genetics*, 84, 740–759. doi:[10.1016/j.ajhg.2009.05.001](https://doi.org/10.1016/j.ajhg.2009.05.001)